

Page 1 of 18  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.05.2018 / 0002  
Replacing version dated / version: 24.05.2017 / 0001  
Valid from: 18.05.2018  
PDF print date: 26.01.2019  
Toko Performance Liquid Paraffin

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

### Toko Performance Liquid Paraffin

**5502041 High Performance Liquid Paraffin yellow 125ml**

**5502042 High Performance Liquid Paraffin red 125ml**

**5502043 High Performance Liquid Paraffin blue 125ml**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Waxes

Sector of use [SU]:

SU21 - Consumer uses: Private households (=general public = consumers)

Chemical product category [PC]:

PC15 - Non-metal-surface treatment products

Environmental Release Category [ERC]:

ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

Brav Germany GmbH, Junkersstr. 1, 82178 Puchheim, Germany

Phone:+49 (0)89 849 369 0, Fax:+49 (0)89 849 369 13

info@brav-germany.com, www.brav-germany.com

Toko AG

Industriestrasse 4

CH-9450 Altstätten SG

Tel.: +41 (0)71 757 73 73 Fax: +41 (0)71 757 73 00

www.toko.ch

www.facebook.com/tokoworldwide

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### Emergency information services / official advisory body:

---

##### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (SWS)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

## 2.2 Label elements

### Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H319-Causes serious eye irritation. H336-May cause drowsiness or dizziness. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.  
 P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area.  
 P312-Call a POISON CENTRE / doctor if you feel unwell.  
 P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
 P501-Dispose of contents / container to special waste collection point.

Propan-2-ol  
 Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

Propan-2-ol	
Registration number (REACH)	01-2119457558-25-XXXX
Index	603-117-00-0
EINECS, ELINCS, NLP	200-661-7
CAS	67-63-0
content %	40-50

Page 3 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.05.2018 / 0002  
 Replacing version dated / version: 24.05.2017 / 0001  
 Valid from: 18.05.2018  
 PDF print date: 26.01.2019  
 Toko Performance Liquid Paraffin

<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
<b>Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b>	
<b>Registration number (REACH)</b>	01-2119471843-32-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	927-241-2 (REACH-IT List-No.)
<b>CAS</b>	---
<b>content %</b>	1-20
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 3, H412

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.  
 If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.  
 Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."  
 Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
 Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.  
 If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.  
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.  
 Danger of aspiration

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effects/damages the central nervous system

Coordination disorders

Mental confusion

Ingestion:

Nausea

Vomiting

Danger of aspiration

Oedema of the lungs

Chemical pneumonitis (condition similar to pneumonia)

#### **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

### **SECTION 5: Firefighting measures**

#### **5.1 Extinguishing media**

##### **Suitable extinguishing media**

CO<sub>2</sub>

Extinguishment powder

Water jet spray

Alcohol resistant foam

##### **Unsuitable extinguishing media**

High volume water jet

#### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

#### **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

### **SECTION 6: Accidental release measures**

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Keep unprotected persons away.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

#### **6.2 Environmental precautions**

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

If accidental entry into drainage system occurs, inform responsible authorities.

#### **6.3 Methods and material for containment and cleaning up**

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

#### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### **7.1 Precautions for safe handling**

##### **7.1.1 General recommendations**

Page 5 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2018 / 0002

Replacing version dated / version: 24.05.2017 / 0001

Valid from: 18.05.2018

PDF print date: 26.01.2019

Toko Performance Liquid Paraffin

Ensure good ventilation.  
 Avoid inhalation of the vapours.  
 Avoid contact with eyes or skin.  
 Keep away from sources of ignition - Do not smoke.  
 Take measures against electrostatic charging, if appropriate.  
 Do not use on hot surfaces.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.  
 Do not store with flammable or self-igniting materials.  
 Observe special storage conditions.  
 Observe special regulations for aerosols!  
 Keep protected from direct sunlight and temperatures over 50°C.  
 Store in a well-ventilated place.  
 Store cool.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 800 mg/m<sup>3</sup>

Chemical Name	Propan-2-ol	Content %:40-50
WEL-TWA: 400 ppm (999 mg/m <sup>3</sup> )	WEL-STEL: 500 ppm (1250 mg/m <sup>3</sup> )	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-122 SA(C) (549 277)</li> <li>- Compur - KITA-150 U (550 382)</li> <li>- Draeger - Alcohol 25/a i-Propanol (81 01 631)</li> <li>- DFG (D) (Loesungsmittelgemische), DFG (E) (Solvent mixtures 6) - 1998, 2002 -</li> <li>- EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004)</li> <li>- Draeger - Alcohol 100/a (CH 29 701)</li> </ul>	
BMGV: ---	Other information: ---	
Chemical Name	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	Content %:1-20
WEL-TWA: 800 mg/m <sup>3</sup>	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul>	
BMGV: ---	Other information: (WEL acc. to RCP-method, EH40)	
Chemical Name	Paraffin wax, fume	Content %:
WEL-TWA: 2 mg/m <sup>3</sup>	WEL-STEL: 6 mg/m <sup>3</sup>	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	
Chemical Name	Dimethoxymethane	Content %:
WEL-TWA: 1000 ppm (3160 mg/m <sup>3</sup> )	WEL-STEL: 1250 ppm (3950 mg/m <sup>3</sup> )	---
Monitoring procedures:	---	

Page 6 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.05.2018 / 0002  
 Replacing version dated / version: 24.05.2017 / 0001  
 Valid from: 18.05.2018  
 PDF print date: 26.01.2019  
 Toko Performance Liquid Paraffin

BMGV: ---

Other information: ---

#### Propan-2-ol

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment, freshwater		PNEC	552	mg/kg	
	Environment - sediment, marine		PNEC	552	mg/kg	
	Environment - soil		PNEC	28	mg/kg	
	Environment - sewage treatment plant		PNEC	2251	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	140,9	mg/l	
Consumer	Human - dermal	Long term	DNEL	319	mg/kg	(1 d)
Consumer	Human - inhalation	Long term	DNEL	89	mg/m3	
Consumer	Human - oral	Long term	DNEL	26	mg/kg	(1 d)
Workers / employees	Human - dermal	Long term	DNEL	888	mg/kg	(1 d)
Workers / employees	Human - inhalation	Long term	DNEL	500	mg/m3	

#### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	900	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1500	mg/m3	

#### Dimethoxymethane

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - water		PNEC	14,577	mg/l	
	Environment - sediment, marine		PNEC	1,4577	mg/l	
	Environment - sediment, freshwater		PNEC	13,135	mg/kg dry weight	
	Environment - sediment, marine		PNEC	1,3135	mg/kg dry weight	
	Environment - soil		PNEC	4,6538	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	10000	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	9,6	mg/kg body weight/day	

Page 7 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.05.2018 / 0002  
 Replacing version dated / version: 24.05.2017 / 0001  
 Valid from: 18.05.2018  
 PDF print date: 26.01.2019  
 Toko Performance Liquid Paraffin

Consumer	Human - inhalation	Long term, systemic effects	DNEL	39	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	5,7	mg/kg body weight/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	22	mg/kg body weight/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	132	mg/m <sup>3</sup>	

(GB) WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. BS EN 14042.  
 BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Chemical resistant protective gloves (EN 374).  
 If applicable  
 Safety gloves made of butyl (EN 374)  
 Protective nitrile gloves (EN 374)  
 Minimum layer thickness in mm:  
 >= 0,5  
 Permeation time (penetration time) in minutes:  
 >= 480  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.  
 Protective hand cream recommended.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
 If OES or MEL is exceeded.  
 Filter A2 P2 (EN 14387), code colour brown, white

Page 8 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.05.2018 / 0002  
 Replacing version dated / version: 24.05.2017 / 0001  
 Valid from: 18.05.2018  
 PDF print date: 26.01.2019  
 Toko Performance Liquid Paraffin

At high concentrations:  
 Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid The propellant is not released when used in accordance with the regulations.
Colour:	Clear
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	~0,75-0,85 (relative density, Active substance )
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	partially, Active substance
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive. When using: development of explosive vapour/air mixture possible.
Oxidising properties:	No

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability



Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

#### Toko Performance Liquid Paraffin

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

#### Propan-2-ol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4570-5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	13900	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	30	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative

Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s): liver
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, vomiting, headaches, fatigue, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>54	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LD50	>20	mg/l/4h	Rat		Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4951	mg/m <sup>3</sup> /4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion, Maximum achievable concentration.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant (Analogous conclusion)
Respiratory or skin sensitisation:				Guinea pig		Not sensitising (Analogous conclusion)
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	No indications of such an effect.
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	No indications of such an effect.
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	No indications of such an effect.



12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

### Propan-2-ol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Leuciscus idus		
12.1. Toxicity to daphnia:	EC50	48h	2285	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:			99,9	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.4. Mobility in soil:	Koc		1,1				Expert judgement
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge		
Other information:	ThOD		2,4	g/g			
Other information:	BOD5		53	%			
Other information:	COD		96	%			References
Other information:	COD		2,4	g/g			
Other information:	BOD		1171	mg/g			

### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>10- <30	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	NOEC/NOEL		>0,1- <=1,0	mg/l			
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,317	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50		>10- 100	mg/l			
12.1. Toxicity to daphnia:	EL50	48h	>22- <46	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

Page 13 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.05.2018 / 0002  
 Replacing version dated / version: 24.05.2017 / 0001  
 Valid from: 18.05.2018  
 PDF print date: 26.01.2019  
 Toko Performance Liquid Paraffin

12.1. Toxicity to algae:	NOELR	72h	<1	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	IC50		>100	mg/l			
12.1. Toxicity to algae:	EL50		>1000	mg/l	Pseudokirchnerie lla subcapitata		
12.2. Persistence and degradability:							Readily biodegradable
12.2. Persistence and degradability:		28d	89	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.2. Persistence and degradability:	ThOD	28d	53-55	%			Biodegradable
12.3. Bioaccumulative potential:	Log Pow		4-5,7				
12.4. Mobility in soil:							Product floats on the water surface.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>1000	mg/l			
Other information:	AOX						Does not contain any organically bound halogens which can contribute to the AOX value in waste water.
Water solubility:			~ 0,04	g/l			Insoluble20°C

Dimethoxymethane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	6990	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	>500	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC10	96h	>500	mg/l	Scenedesmus subspicatus		
12.2. Persistence and degradability:			>80	%			Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0				
Toxicity to bacteria:	EC10	17h	3000	mg/l	Pseudomonas putida		
Water solubility:			32,3	%			

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

Page 14 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.05.2018 / 0002  
 Replacing version dated / version: 24.05.2017 / 0001  
 Valid from: 18.05.2018  
 PDF print date: 26.01.2019  
 Toko Performance Liquid Paraffin

The waste codes are recommendations based on the scheduled use of this product.  
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)  
 16 05 04 gases in pressure containers (including halons) containing hazardous substances  
 Recommendation:  
 Sewage disposal shall be discouraged.  
 Pay attention to local and national official regulations.  
 Take full aerosol cans to problem waste collection.  
 Take emptied aerosol cans to valuable material collection.

**For contaminated packing material**

Pay attention to local and national official regulations.  
 Recommendation:  
 Do not perforate, cut up or weld uncleaned container.  
 Recycling  
 15 01 04 metallic packaging

**SECTION 14: Transport information**

**General statements**

14.1. UN number: 1950

**Transport by road/by rail (ADR/RID)**

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Classification code: 5F

LQ: 1 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code: D



**Transport by sea (IMDG-code)**

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

EmS: F-D, S-U

Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable



**Transport by air (IATA)**

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

14.5. Environmental hazards: Not applicable



**14.6. Special precautions for user**

Persons employed in transporting dangerous goods must be trained.  
 All persons involved in transporting must observe safety regulations.  
 Precautions must be taken to prevent damage.

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Freighted as packaged goods rather than in bulk, therefore not applicable.  
 Minimum amount regulations have not been taken into account.  
 Danger code and packing code on request.  
 Comply with special provisions.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Observe restrictions:  
 Comply with trade association/occupational health regulations.

Page 15 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 18.05.2018 / 0002  
 Replacing version dated / version: 24.05.2017 / 0001  
 Valid from: 18.05.2018  
 PDF print date: 26.01.2019  
 Toko Performance Liquid Paraffin

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): ~ 95 %

Observe incident regulations.

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 8, 15  
 Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

## Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H412 Harmful to aquatic life with long lasting effects.

Eye Irrit. — Eye irritation  
 Asp. Tox. — Aspiration hazard  
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects  
 Aerosol — Aerosols  
 Flam. Liq. — Flammable liquid  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic

## Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to  
ACGIH American Conference of Governmental Industrial Hygienists  
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
AOEL Acceptable Operator Exposure Level  
AOX Adsorbable organic halogen compounds  
approx. approximately  
Art., Art. no. Article number  
ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)  
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
BCF Bioconcentration factor  
BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)  
BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)  
BMGV Biological monitoring guidance value (EH40, UK)  
BOD Biochemical oxygen demand  
BSEF Bromine Science and Environmental Forum  
bw body weight  
CAS Chemical Abstracts Service  
CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids  
CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques  
CIPAC Collaborative International Pesticides Analytical Council  
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
CMR carcinogenic, mutagenic, reproductive toxic  
COD Chemical oxygen demand  
CTFA Cosmetic, Toiletry, and Fragrance Association  
DMEL Derived Minimum Effect Level  
DNEL Derived No Effect Level  
DOC Dissolved organic carbon  
DT50 Dwell Time - 50% reduction of start concentration  
DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)  
dw dry weight  
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
EC European Community  
ECHA European Chemicals Agency  
EEA European Economic Area  
EEC European Economic Community  
EINECS European Inventory of Existing Commercial Chemical Substances  
ELINCS European List of Notified Chemical Substances  
EN European Norms  
EPA United States Environmental Protection Agency (United States of America)  
ERC Environmental Release Categories  
ES Exposure scenario  
etc. et cetera  
EU European Union  
EWC European Waste Catalogue  
Fax. Fax number  
gen. general  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
HET-CAM Hen's Egg Test - Chorionallantoic Membrane  
HGWP Halocarbon Global Warming Potential  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC Intermediate Bulk Container  
IBC (Code) International Bulk Chemical (Code)  
IC Inhibitory concentration  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
LC lethal concentration



Page 17 of 18  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.05.2018 / 0002  
Replacing version dated / version: 24.05.2017 / 0001  
Valid from: 18.05.2018  
PDF print date: 26.01.2019  
Toko Performance Liquid Paraffin

LC50 lethal concentration 50 percent kill  
LCLo lowest published lethal concentration  
LD Lethal Dose of a chemical  
LD50 Lethal Dose, 50% kill  
LDLo Lethal Dose Low  
LOAEL Lowest Observed Adverse Effect Level  
LOEC Lowest Observed Effect Concentration  
LOEL Lowest Observed Effect Level  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NIOSH National Institute of Occupational Safety and Health (United States of America)  
NOAEC No Observed Adverse Effective Concentration  
NOAEL No Observed Adverse Effect Level  
NOEC No Observed Effect Concentration  
NOEL No Observed Effect Level  
ODP Ozone Depletion Potential  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PAH polycyclic aromatic hydrocarbon  
PBT persistent, bioaccumulative and toxic  
PC Chemical product category  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
POCP Photochemical ozone creation potential  
ppm parts per million  
PROC Process category  
PTFE Polytetrafluorethylene  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SADT Self-Accelerating Decomposition Temperature  
SAR Structure Activity Relationship  
SU Sector of use  
SVHC Substances of Very High Concern  
Tel. Telephone  
ThOD Theoretical oxygen demand  
TOC Total organic carbon  
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).  
WHO World Health Organization  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 18.05.2018 / 0002  
Replacing version dated / version: 24.05.2017 / 0001  
Valid from: 18.05.2018  
PDF print date: 26.01.2019  
Toko Performance Liquid Paraffin

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.